



NOTES:

1. MODEL 3056 ACCELEROMETER MOUNT SYSTEM PROVIDES MOUNTS AT FRONT, TOP, REAR, LEFT SIDE AND CENTER (HEAD C-G) LOCATIONS.
2. DIMENSIONS GIVEN ARE FOR ENDEVCO 7264-2000 ACCELEROMETERS ONLY.
3. THE TOP, FRONT, LEFT AND REAR MOUNTS ARE INTERCHANGEABLE.
4. POSITION ACCURACY OF BLOCKS IN HEAD  $\pm 0.05$
5. POSITION ACCURACY OF SEISMIC MASS WITHIN ACCELEROMETER  $\pm 0.03$  (PER ENDEVCO SPEC.)
6. CENTER OF GRAVITY (C-G) LOCATIONS PER G.M. DRAWINGS 78051-61 AND 78051-338 FOR HYBRID III TEST DUMMY HEAD

B	WAS B-3056	10/99
A	ADD SIDE MOUNT	12/98
SYM	REVISION	DATE

<b>FREE MOTION HEAD FORM</b>	
ACCELEROMETER HEAD MOUNT FOR 7264 ACCELEROMETERS	
SCALE: .75X	DRAWN BY: C.R. MORGAN
DATE: 3JUN94	MODEL: 3056
UNLESS OTHERWISE SPECIFIED	
TWO PLACE DECIMALS $\pm .010$	SURFACE FINISH 125 ✓
THREE PLACE DECIMALS $\pm .005$	REMOVE ALL BURRS & SHARP EDGES
ANGLES $\pm 0' 30"$	DIMENSION LIMITS HELD AFTER PLATING
<b>ROBERT A. DENTON, INC.</b>	
ROCHESTER HILLS, MICHIGAN	
DRAWING NUMBER: <b>B-3056-D</b>	